



## Latitude Edge 8' Cable SRL-P

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Durable stainless steel housing with nylon sides.
- Frameless design creates thinner housing size.
- Exclusive dorsal attachment bracket with SRL separator feature.
- Compact shock pack design with harness restraint strap.
- 360/180° attachment point offers full range of motion.
- Side payout for smooth retraction.
- Protective label cover for product longevity and traceability.
- RFID equipped.
- Designed for sharp leading edges with foot-level connection.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class  
**2**  
Anchor above or below dorsal D-ring

Product shown:  
023-5350

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 36 in. (91 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 6 in. (2 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 83 in. (211 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	15 ft. 5 in. (4.7 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Cable	3/16" galvanized steel
Bracket	Steel and aluminum
Housing	Stainless steel and nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester



## Latitude Edge 8' Cable SRL-P



**Standards:** ANSI Z359.14-2021  
OSHA 1910.140 & 1910.66

**Capacity:** ANSI 130-310 lbs. (59-141 kg)  
OSHA Up to 420 lbs. (191kg)

### CONNECTOR

### ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D)	SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	CONNECTOR																			ATTACHMENT												
								L Steel Swivel Snap Hook ①	AlU Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	L Steel Swivel Rebar Hook ⑤	Steel Rebar Hook ⑥	L Steel Swivel Rebar Hook ⑦	Steel Swivel Rebar Hook ⑧	Steel Capitive Eye Carabiner ⑨	AlU Rebar Hook ⑩	AlU Capitive Eye Carabiner ⑪	AlU Swivel Carabiner ⑫	No Attachment ⑬	Trip Lock Steel Carabiner ⑭	AlU Capitive Eye Carabiner ⑮	AlU Carabiner ⑯	AlU Snap Hook ⑰	Cap Mount Bracket FS-EX313 ⑱	Soft Loop ⑲	Integrated BWR ⑳	ID14 BWR ㉑	9012 BWR ㉒	9013 BWR ㉓									
023-5350	2	S	8	Steel Cable	Ø3/16	Nylon/SS	4.4	X																												X			
023-5351	2	S	8	Steel Cable	Ø3/16	Nylon/SS	5.2						X																								X		
023-5352	2	S	8	Steel Cable	Ø3/16	Nylon/SS	4.1		X																												X		
023-5353	2	S	8	Steel Cable	Ø3/16	Nylon/SS	5.0										X																				X		
023-5354	2	S	8	Steel Cable	Ø3/16	Nylon/SS	3.9														X																X		
023-5355	2	D	8	Steel Cable	Ø3/16	Nylon/SS	7.7	X																													X		
023-5356	2	D	8	Steel Cable	Ø3/16	Nylon/SS	9.2							X																							X		
023-5357	2	D	8	Steel Cable	Ø3/16	Nylon/SS	7.1		X																												X		
023-5358	2	D	8	Steel Cable	Ø3/16	Nylon/SS	8.8														X																X		
023-5359	2	D	8	Steel Cable	Ø3/16	Nylon/SS	7.0																														X		

