



SAFEWAZE



Rescue Ladder
Model: FS-EX243-BL
18ft (5.48m)



IMPORTANT!

ALL PERSONS USING THIS EQUIPMENT MUST READ AND UNDERSTAND ALL INSTRUCTIONS. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY OR DEATH. USERS SHOULD BE FAMILIAR WITH PERTINENT REGULATIONS GOVERNING THIS EQUIPMENT. ALL INDIVIDUALS WHO USE THIS PRODUCT MUST BE PROPERLY INSTRUCTED ON HOW TO USE THIS DEVICE.

Read This Instruction Manual Carefully Before Using This Equipment.

User Instructions must always be available to the user and are not to be removed except by the user of this equipment. For proper use, see supervisor, User Instructions, or contact the manufacturer.

WARNING

Compliant fall protection and emergency rescue systems help prevent serious injury during fall arrest. Users and purchasers of this equipment must read and understand the User Instructions provided for correct use and care of this product. All users of this equipment must understand the instructions, operation, limitations and consequences of improper use of this equipment and be properly trained prior to use per OSHA 29 CFR 1910.66 and 1926.503 or applicable local standards. **Misuse or failure to follow warnings and instructions may result in serious personal injury or death.**

PURPOSE

The FS-EX243-BL is a rescue system designed to return fall victims to safety. Deploy ladder kit using the existing anchor or new anchor location. The ladder kit allows a capable fall victim to climb to safety. Any reference to "rescue system" in this manual include, and apply to the FS-EX243-BL.

USE INSTRUCTIONS

1. A user must be trained to properly and safely use this equipment in normal and emergency situations. Users must have a physician ensure they are clear of any medical conditions that may affect the proper and safe use of this equipment.
2. Do not use/install equipment without proper training by a "competent person" as defined by OSHA 29 CFR 1926.32(f).
3. Before using a rescue system, user must be trained in accordance with the requirements of OSHA 29 CFR 1910.66 in the safe use of the system and its components.
4. Use only with ANSI/OSHA compliant personal fall arrest or restraint systems. The anchorage must have the strength capable of supporting a static load, applied in the directions permitted by the system, of at least 5,000-lbf (22kN) in the absence of certification.
5. Use of this product must be approved by an engineer or other qualified person to be compatible with any and all structural & operational characteristics of the selected installation location and system to be connected to this rescue system **Improper use may result in serious personal injury or death.**
6. The rescue ladder system must be inspected prior to each use for wear, damage, and other deterioration. If defective components are found the system must be immediately removed from service in accordance with the requirements of OSHA 29 CFR 1910.66 and 1926.502.
7. A rescue plan, and the means at hand to implement it, must be in place that provides the prompt rescue of users in the event of a fall, or assures that users are able to rescue themselves.

USE LIMITATIONS: The Rescue Ladder system shall not be used outside its limitations, or for any purpose other than which it is intended. The Rescue Ladder must be retired from use after rescue has been executed.


1. The rescue system is designed for single user, with a capacity up to 310-lbs (140 kg) including clothing, tools, etc.
2. The rescue system is designed to be used in temperatures ranging from -40°F to +130°F (-40°C to +54°C).
3. Do not expose the rescue ladder system to chemicals or harsh solutions which may have a harmful effect.
4. Do not alter or modify this product in anyway.
5. Caution must be taken when using any component of a fall protection, work positioning, rope access, or rescue system near moving machinery, electrical hazards, sharp edges, or abrasive surfaces, as contact may cause equipment failure, personal injury, or death.
6. Do not remove the labeling from this product.
7. Additional requirements and limitations may apply depending on anchorage type and fastening option utilized for installation. All placements must be approved by an engineer or other qualified person. **Improper use may result in serious personal injury or death.**

COMPATIBILITY LIMITATIONS

The rescue ladder system must only be coupled to compatible connectors. OSHA 29 CFR 1926.502 prohibits snaphooks from being engaged to certain objects unless two requirements are met: it must be a locking type snaphook, and it must be "designed for" making such a connection. "Designed for" means that the manufacturer of the snaphook specifically designed the snaphook to be used to connect to the equipment listed. The following connections must be avoided, because they can result in rollout* when a non-locking snaphook is used:

- Direct connection of a snaphook to horizontal lifeline.
- Two (or more) snaphooks connected to one D-ring.
- Two snaphooks connected to each other.
- A snaphook connected back on its integral lanyard.
- A snaphook connected to a webbing loop or webbing lanyard.
- Improper dimensions of the D-ring, rebar, or other connection point in relation to the snaphook dimensions that would allow the snaphook keeper to be depressed by a turning motion of the snaphook.

***Rollout: A process by which a snaphook or carabiner unintentionally disengages from another connector or object to which it is coupled. (ANSI Z359.0-2007)**



Step 1




Assessment:

Check fall victim for consciousness. (Worker must verbally respond and be uninjured and able to climb. If worker is injured or unconscious a trained rescue response team must perform rescue and use proper equipment.) If worker is conscious, know how and where the ladder will be deployed.

! WARNING: Rescuer must follow all personal fall protection guidelines.

Step 2




Anchoring:

If anchor is damaged use the nearest anchor that allows the ladder to be within close proximity of victim after deployed.

! Warning: Anchor and structure must be able to support 5,000-lbf or (22kN). Only use an approved ANSI Z359.18 Anchorage.

Step 3




Deployment:

Once the rescue ladder system is anchored drop the bag to deploy the Rescue Ladder. Avoid hitting the fall victim while deploying the ladder.

FOR EASE OF USE: Have victim climb in direct line of rope grab.

Step 4




Recovery:

Instruct fall victim to attach the rope end carabiner to the D-ring of their harness. Do not remove original fall protection restraint. Once the fall victim is on the ladder, rescuer must remove excess slack by pulling rope through the rope grab device. Do not attempt to hoist the fall victim but always keep rope taut as worker climbs the Rescue Ladder.

TO PREVENT HIGH IMPACT SECONDARY FALL: Continuously remove slack as victim climbs rope ladder

Step 5



Marking:

Remove deployed tag from bottom rung of ladder and return all other components to deployment bag. Close deployment bag and mark rescue ladder as deployed by attaching deployment tag to handle and loop created by closing deployment bag.

***Note:** Once rescue ladder has been deployed it may not be re-used until properly re-packed by the manufacturer. Rescue ladder must be shipped to the manufacturer or disposed of properly.



MAINTENANCE, CLEANING AND STORAGE

If stored as directed and returned to the manufacturer for inspection and re-packing as directed, there is no maintenance requirement as this would require un-packing the rescue ladder. Do not use any corrosive chemicals that could damage the product. Use compressed air to clean only. Store in a cool, dry, clean environment, out of direct sunlight and free of corrosive or other degrading elements.

Note: A plan must be in place to ensure that the rescue ladder remains in good working condition throughout the life of the product. This should include but not be limited to long term storage with or without use.

RESCUE LADDER BAG LABELING



Ladder Rescue Kit
18' (5.48m) Rescue Ladder System
Model: FS-EX243-BL

Check fall victim for consciousness:

- Worker verbally responsive.**
- Uninjured and able to climb.**

*This ladder system is only used on a coherent uninjured worker. If worker is injured or unconscious a trained rescue response team must perform rescue.



SAFEWAZE
Rescue Ladder Kit
18' (5.48m) Rescue Ladder System
Model: FS-EX243-BL
(Max Capacity 310-lbs)

Compliance:
 OSHA 1910.66 / OSHA 1926.503

Material:
 Zinc Alloy Steel, Aluminum, Nylon Webbing
 Kernmantle Nylon Rope


IMPORTANT!
ALL PERSONS USING THIS EQUIPMENT MUST READ AND UNDERSTAND ALL INSTRUCTIONS. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY OR DEATH. USERS SHOULD BE FAMILIAR WITH PERTINENT REGULATIONS GOVERNING THIS EQUIPMENT. ALL INDIVIDUALS WHO USE THIS PRODUCT MUST BE PROPERLY INSTRUCTED ON HOW TO USE THIS DEVICE. AVOID CONTACT WITH SHARP EDGES, ABRASIVE SURFACES, AND PHYSICAL HAZARDS (THERMAL, CHEMICAL, ELECTRICAL, ETC.)

RSL-XXX


(US Patent Pending)

MFD: mm/yyyy


1 ANCHOR & DROP
(Rescuer)




2 CLIP-IN
(Victim)



3 PULL SLACK
(Rescuer)



ROPE GRAB (RGS) LABELING



RESCUE LADDER

18' (5.48m) Rescue Ladder System



IMPORTANT!

ALL PERSONS USING THIS EQUIPMENT MUST READ AND UNDERSTAND ALL INSTRUCTIONS. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY OR DEATH. USERS SHOULD BE FAMILIAR WITH PERTINENT REGULATIONS GOVERNING THIS EQUIPMENT. ALL INDIVIDUALS WHO USE THIS PRODUCT MUST BE PROPERLY INSTRUCTED ON HOW TO USE THIS DEVICE. DO NOT ALTER OR MODIFY THIS PRODUCT IN ANY WAY. USE WITH INCLUDED COMPONENTS AS DIRECTED ONLY.

INSPECTION AND MAINTENANCE LOG

MODEL NUMBER: _____

DATE OF MANUFACTURE: _____

Date	Part Number	Comments	Inspector Name

Inspection:

Inspection must be made at least semi-annually. The inspection must be performed by a competent person other than the user. If harsh conditions exist then inspections must be carried out more frequently. All inspection results must be logged in the space provided above. (It is recommended that the anchor device be marked with the date of the next or last inspection.)

1. Make sure all labeling is affixed to the unit.
2. Inspect rescue ladder system for signs of damage or wear.
3. Ensure all components are in the bag.
4. Ensure rope and ladder are not tangled.
5. Record inspection results in the space provided above.

If any damage that could affect the strength or operation of the device, or unsafe conditions are found, proper disposal is required. The rescue system must be rendered unusable and then properly discarded.

Product Warranty, Limited Remedy and Limitation of Liability

WARRANTY: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Equipment offered by Safewaze is warranted against factory defects in workmanship and materials for a period of one year from date of purchase or first use by the original owner.

LIMITED REMEDY: Upon notice in writing, Safewaze will repair or replace all defective items at Safewaze USA's sole discretion. Safewaze reserves the right to require that the defective item be returned to its plant for inspection before determining the appropriate course action. Warranty does not cover equipment damage resulting from wear, abuse, damage in transit, failure to maintain the product or other damage beyond the control of Safewaze shall be the sole judge of product condition and warranty options. This warranty applies only to original purchaser and is the only warranty applicable to this product. Please contact Safewaze technical service department for assistance.

LIMITATION OF LIABILITY: IN NO EVENT WILL SAFEWAZE BE LIABLE FOR ANY INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES INCLUDING, BUT NOT LIMITED TO LOSS OF PROFITS, IN ANY WAY RELATED TO THE PRODUCTS REGARDLESS OF THE LEGAL THEORY ASSERTED.

SAFEWAZE

322 Industrial Court, Concord, NC 28025

1(704) 262-7893 / www.safewaze.com