



TECHNICAL DATA SHEET

safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

018-5007

7' Web Retractable w/
Aluminum Locking Rebar Hook



Features and Benefits

Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The 018-5007 features a unique clear plastic housing for enhanced unit inspection and a revolutionary internal braking system, which alleviates the need for an external shock pack in such a small, ergonomic SRL. Fall indicator is sewn into webbing.

Length of Web 7 ft (2.13 m)

Weight of Unit 3.3 lbs (1.50 kg)

Materials High-strength clear plastic housing
.77 in (19.5 mm) Ultrahigh Molecular Weight Webbing
Aluminum rebar hook
Steel carabiner included

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength
3,600 lbs (1632 kg) Gate Rated

Maximum Arresting Force <1,800 lbs (816.47 kg)

Maximum Arrest Distance Class A up to 24 in (60.96 cm) if used above Dorsal D-ring
Class B up to 54 in (137.16 cm) if used up to a maximum of 2 ft below Dorsal D-ring

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)
OSHA up to 420 lbs (190.51 kg)

Webbing Tensile Strength 4,200 lbs (1905.09 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32