



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

### FS-EX235

Fall Protection Removable / Reusable  
Mining Friction Rock Bolt Anchor



<b>Description</b>	Fall Protection removable / reusable Mining friction rock bolt anchor. Easy installation and removal. Must follow installation instructions for proper installation. Can be used in horizontal, vertical and overhead applications.
<b>Length</b>	17 in (431.8 mm)
<b>Diameter</b>	1.5 in (39 mm)
<b>Materials</b>	Main Cable, Return Wire - Aircraft Cable Spoons, Stop Sleeve, End Termination - Stainless Steel Trigger - Aluminum Spring - Zinc Plated Steel Swage - Zinc Plated Copper Thimble Loop - Powder Coated Steel
<b>Minimum Tensile Strength</b>	10,000 lbs - 44 kN
<b>Weight</b>	1.2 lbs (544.3 g)
<b>Weight Capacity</b>	310 lbs (140.61 kg) - Single user
<b>Applicable Standards</b>	Meets OSHA 1926.502 - ANSI Z359.1 - ANSI Z359.7

**\*Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.**