



TECHNICAL DATA SHEET

safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
 322 Industrial Court, Concord, NC 28025

FS-FSP1407-W-RBH 7' CLASS A Web Retractable w/ Locking Rebar Hook



Features and Benefits Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The FS-FSP1407-W-RBH features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall. Fall indicator sewn into webbing.

Length of Web 7 ft (2.13 m)

Weight of Unit 3.75 lbs (3.79 kg)

Materials Aluminum housing
 1 in (25.4 mm) Ultrahigh Molecular Weight webbing w/ sewn-in fall indicator
 Forged steel rebar hook
 Steel carabiner

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength
 3,600 lbs (1632 kg) Gate Rated

Arresting Force Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)

Maximum Arrest Distance <24 in (609.6 mm)

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)
 OSHA up to 420 lbs (190.51 kg)

Webbing Tensile Strength 4,200 lbs (1905.09 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32