



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

FS-FSP1409-W 9' CLASS A Web Retractable w/ Locking Snap Hook



Features and Benefits	Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The FS-FSP1409-W features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall. Fall indicator sewn into webbing.
Length of Web	9 ft (2.74 m)
Weight of Unit	3.05 lbs (1.38 kg)
Materials	Aluminum housing 1 in (25.4 mm) Ultrahigh Molecular Weight webbing w/ sewn-in fall indicator Forged steel snap hook Steel carabiner Steel O-ring
Hook Ratings	5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated
Arresting Force	Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)
Maximum Arrest Distance	<24 in (609.6 mm)
Maximum Working Load	ANSI 130-310 lbs (58.97-140.61 kg) OSHA up to 420 lbs (190.51 kg)
Webbing Tensile Strength	4,200 lbs (1905.09 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32