



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET



### SW-8008-11LE-ALU-DL 11' Dual Leg LE Cable Retractable

<b>Features and Benefits</b>	Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The SW-8008-11LE-ALU-DL features mobility-enhancing swivel-tops, rugged and durable housings, and a unique energy absorption system built into the dual leg back pad.
<b>Length of Cable</b>	11 ft (3.35 m)
<b>Weight of Unit</b>	8.80 lbs (3.99 kg)
<b>Materials</b>	High-strength polymer housings 0.19 in (4.82 mm) Galvanized steel cable Aluminum Snap Hooks
<b>Hook Ratings</b>	5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated
<b>Arresting Force</b>	<b>NON-LE USE:</b> Max Force < 1,800 lbs (816.47 kg); Avg Force < 1,350 lbs (612.35 kg) <b>LE USE:</b> Max Force < 1,800 lbs (816.47 kg); Avg Force < 900 lbs (408.23 kg)
<b>Maximum Arrest Distance</b>	<b>NON-LE USE: (Class A)</b> Arresting distance 24 in (60.96 cm) <b>LE USE: (Class B)</b> Arresting distance 54 - 102 in (1.37 - 2.59 m)
<b>Maximum Working Load</b>	<b>NON-LE USE:</b> ANSI, 130-310 lbs (58.96-140.61 kg) OSHA, up to 420 lbs (190.51 kg) <b>LE USE:</b> 310 lbs (140.61 kg)
<b>Cable Tensile Strength</b>	3,700 lbs (1678.29 kg)
<b>Applicable Standards</b>	Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32