



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET



SW-8008-11LE-DL 11' Dual Leg LE Cable Retractable

Features and Benefits	Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The SW-8008-11LE-DL features mobility-enhancing swivel-tops, rugged and durable housings, and a unique energy absorption system built into the dual leg back pad.
Length of Cable	11 ft (3.35 m)
Weight of Unit	9.40 lbs (4.26 kg)
Materials	High-strength polymer housings 0.19 in (4.82 mm) Galvanized steel cable Steel Snap Hooks
Hook Ratings	5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated
Arresting Force	NON-LE USE: Max Force < 1,800 lbs (816.47 kg); Avg Force < 1,350 lbs (612.35 kg) LE USE: Max Force < 1,800 lbs (816.47 kg); Avg Force < 900 lbs (408.23 kg)
Maximum Arrest Distance	NON-LE USE: (Class A) Arresting distance 24 in (60.96 cm) LE USE: (Class B) Arresting distance 54 - 102 in (1.37 - 2.59 m)
Maximum Working Load	NON-LE USE: ANSI, 130-310 lbs (58.96-140.61 kg) OSHA, up to 420 lbs (190.51 kg) LE USE: 310 lbs (140.61 kg)
Cable Tensile Strength	3,700 lbs (1678.29 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32