



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

### FS-EX112

Fall Protection Removable / Reusable  
Toggle Lok Bolt Anchor



<b>Description</b>	Fall Protection removable / reusable Toggle Lok Bolt anchor. Easy installation and removal. Must follow installation instructions for proper installation. Can be used in horizontal, vertical and overhead applications.
<b>Length</b>	13.75 in (349 mm)
<b>Diameter</b>	3/4 in (19 mm)
<b>Materials</b>	Main Cable, Activator Wire - Aircraft Cable Toggle Bar - Stainless Steel Hole Plug, Trigger - Aluminum Spring - Zinc Plated Steel Swage - Zinc Plated Copper Loop Cover - Polyurethane
<b>Static Tensile Strength</b>	5,000 lbf - 22.25 kN
<b>Weight</b>	0.45lbs (204 g)
<b>Weight Capacity</b>	310 lbs (140.61 kg) - Single user
<b>Applicable Standards</b>	Meets OSHA 1926.502 - OSHA 1910.66 - ANSI Z359.1

**\*Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.25kN) pounds per employee attached.**