



## TECHNICAL DATA SHEET

[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

### FS-FSP1409-W-DL-RBH 9' CLASS A Dual Leg Web Retractable w/ Forged Steel Rebar Hooks



#### Features and Benefits

Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The FS-FSP1407-W-DL-RBH features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall. Fall indicator sewn into webbing.

**Length of Web** 9 ft (2.74 m)

**Weight of Unit** 8.25 lbs (3.74 kg)

#### Materials

Aluminum housings  
1 in (25.4 mm) Ultrahigh Molecular Weight webbing w/ sewn-in fall indicator  
Forged steel rebar hooks  
Steel carabiner  
Steel O-rings

**Hook Ratings** 5,000 lbs (2267.96 kg) Tensile Strength  
3,600 lbs (1632 kg) Gate Rated

**Arresting Force** Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)

**Maximum Arrest Distance** <24 in (609.6 mm)

**Maximum Working Load** ANSI 130-310 lbs (58.97-140.61 kg)  
OSHA up to 420 lbs (190.51 kg)

**Webbing Tensile Strength** 4,200 lbs (1905.09 kg)

**Applicable Standards** Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32