



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET



### FS-FSP1420-W 20' CLASS B Web Retractable w/ Locking Snap Hook

|                                 |  |
|---------------------------------|--|
| <b>Features and Benefits</b>    | Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The FS-FSP1420-W features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall. Fall indicator sewn into webbing. |
| <b>Length of Web</b>            | 20 ft (6.10 m)   |
| <b>Weight of Unit</b>           | 5.65 lbs (2.56 kg)   |
| <b>Materials</b>                | High Strength Polymer Housing<br>1 in (25.4 mm) Ultrahigh Molecular Weight webbing w/ sewn-in fall indicator<br>Forged steel snap hook<br>Steel carabiner  |
| <b>Hook Ratings</b>             | 5,000 lbs (2267.96 kg) Tensile Strength<br>3,600 lbs (1632 kg) Gate Rated  |
| <b>Arresting Force</b>          | Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)   |
| <b>Maximum Arrest Distance</b>  | <54 in (1371.6 mm)   |
| <b>Maximum Working Load</b>     | 310 lbs (140.61 kg)  |
| <b>Webbing Tensile Strength</b> | 4,200 lbs (1905.09 kg)   |
| <b>Applicable Standards</b>     | Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32   |