



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

### FS66150

6' Dual-Leg Shock Lanyard Combo  
w/ O-Ring & Rebar Hook



<b>Features and Benefits</b>	Fall arrest lanyard with two rebar hooks (connect to anchor point) and one snap hook (connects to dorsal harness D-ring). Elastic webbing. External D-ring allows for SRL attachment to convert to dual-purpose unit. Works independently allowing for proper component functionality.
<b>Length</b>	4 ft (1.22 m) to 6 ft (1.83 m)
<b>Weight</b>	6.35 lbs (2.88 kg)
<b>Weight Capacity</b>	310 lbs (140.61 kg)
<b>Attachment Point(s)</b>	1 Snap hook - 2 Rebar hooks - 1 D-ring
<b>Materials</b>	1.94 in (49.28 mm) Tubular polyester webbing w/ 1 in (25.4 mm) core High-strength polyester stitching Shock absorber Forged steel snap hook and two (2) rebar hooks: 3,600 lbs Gate-rated; Min breaking strength > 5,000 lbs
<b>Applicable Standards</b>	Meets OSHA 1926.502 - ANSI Z359.13 - ANSI A10.32