



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

FS873

Deluxe Swivel Roof Anchor
w/ D-Ring and Slot for Retractable



Description	The Safewaze™ deluxe swivel roof anchor is a rated roof anchor point designed for wood or metal roofs. The requirement for wood decking is 0.75 in (19.05 mm) plywood or thicker and for metal decking, 20 gauge or thicker. Any attachment material must be rated to meet OSHA, federal, state, and local government regulations for fall protection anchor points.
Base Dimensions	10 in X 10 in (254 mm X 254 mm)
Number of Holes in Base	10
Required Fasteners	(10) 1-5/8" #8 Grip Rite Screws
Pole Height	8 in (203.2 mm)
Material	Carbon Steel
Working Load	400 lbs (181.44 kg) - Designed for single person use
Minimum Tensile Strength	5,000 lbs (2267.96 kg)
Weight	17 lbs (7.71 kg) (without SRL)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.1 - ANSI A10.32

***Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.**