



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

FS880

4' Concrete Anchor Strap
w/ Wear Pad, D-ring and Sewn Eye



Description	Heavy-duty concrete anchor strap with wear sleeve, one soft-eye loop, and one D-ring
Length	4 ft (1.22 m) (other lengths available)
Weight	0.45 lbs (0.2 kg)
Weight Capacity	310 lbs (140.61 kg)
Attachment Point(s)	1 D-ring - 1 Soft-eye loop
Materials	1.75 in (44.45 mm) Polyester webbing 24 in (609.6 mm) wear sleeve Forged steel D-ring
Minimum Breaking Load	5,000 lbs (2267.96 kg)
Applicable Standards	Meets OSHA 1910/1926.502 - ANSI Z359.18 - ANSI A10.32

FS880
 4' Concrete Anchor Strap w/ Wear Pad, D-ring and Sewn Eye

INSTALLATION INSTRUCTIONS

▲ WARNING!!!!▲

FAILURE TO READ AND UNDERSTAND THESE INSTALLATION INSTRUCTIONS MAY RESULT IN SERIOUS INJURY OR DEATH

ENSURE THAT THE FS880 CONCRETE ANCHOR STRAP HAS NOT BEEN DAMAGED DURING SHIPPING PRIOR TO USE.

THE FS880 IS AN ENGINEERED PRODUCT. IF DAMAGED, IT MUST BE REMOVED FROM SERVICE AND RETURNED TO THE ORIGINAL SUPPLIER FOR REPLACEMENT IF REQUIRED.

SYNTHETIC STRAPS SHOULD NOT BE USED IN EXCESS OF 200° F TO AVOID DAMAGE FROM HEAT, WELDING SPLATTER/SPARKS, AND CORROSIVE CHEMICALS.

IMPORTANT!!!!

CAREFULLY READ ALL INSTALLATION AND SPECIFICATION INSTRUCTIONS REGARDING THE USE OF THIS PRODUCT.

PRIOR TO ATTACHMENT OF A FS880 CONCRETE ANCHOR STRAP TO ANY ELEMENT OF A PROJECT, THE ELEMENT SHALL BE SO FRAMED, FASTENED, TIED, AND BRACED, SO AS TO PROVIDE THE REQUIRED STRENGTH AND RIGIDITY.

THE FS880 CONCRETE ANCHOR STRAP SHALL BE USED ACCORDING TO THE MANUFACTURERS SPECIFICATIONS UNDER THE SUPERVISION OF A COMPETENT PERSON TRAINED IN ITS PROPER USE.

THE FS880 CONCRETE ANCHOR STRAP IS A COMPONENT OF A FALL ARREST SYSTEM. LOCATIONS FOR PLACEMENT OF THE STRAP MAY VARY, AND SPECIFIC PROCEDURES FOR UTILIZATION WILL BE REQUIRED TO ENSURE ADEQUATE FALL PROTECTION FOR WORKERS.

