safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET



FS-EX213

Hybrid Mega Swivel 10K Anchor

Description	Fall Protection removable / reusable Hybrid Mega Swivel anchor. Easy installation and removal. Must follow installation instructions for proper installation. Can be used in horizontal, vertical and overhead applications.
Length	6.25 in (158.75 mm)
Diameter	1 in (25.4 mm)
Materials	Return Wire - Aircraft Cable Cone, Spoons - Stainless Steel Retaining Bushing, Bolt, Sleeve, Swivel - Zinc Plated Steel Compression Bushing - Polyethylene
Minimum Tensile Strength	10,000 lbs - 44 kN
Weight	2.10 lbs (952.5 g)
Weight Capacity	ANSI 310 lbs (140.61 kg) - Single user OSHA 420 lbs (191 kg) - Single user
Applicable Standards	Meets OSHA 1926.502 - OSHA 1910.66 ANSI Z359.18 (Type T) - ANSI Z359.7-2011

***Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.**