



TECHNICAL DATA SHEET

safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

SW-8008-10-RBH-DL 10' CLASS A Dual Leg Cable Retractable



| | |
|--------------------------------|---|
| Features and Benefits | Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The SW-8008-10-RBH-DL features mobility-enhancing swivel-tops, rugged and durable housings, and a unique braking system that eases shock in the event of a fall. |
| Length of Cable | 10 ft (3.05 m) |
| Weight of Unit | 11.10 lbs (5.03 kg) |
| Materials | High-strength polymer housing 0.19 in (4.82 mm) Galvanized steel cable Forged steel rebar hooks |
| Hook Ratings | 5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated |
| Arresting Force | Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg) |
| Maximum Arrest Distance | Arresting distance <24 in (609.60 mm) |
| Maximum Working Load | ANSI 130-310 lbs (58.97-140.61 kg) OSHA up to 420 lbs (190.51 kg) |
| Cable Tensile Strength | 3,700 lbs (1678.29 kg) |
| Applicable Standards | Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32 |