



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET



6' Web Personal SRD Series

Features and Benefits The Safewaze™ 6' Personal SRD's are designed to be used as a single-person fall protection device. All configurations of the series feature a unique plastic housing for durability and enhanced service life. Fall indicator is incorporated into shock pack

Length of Web 6 ft (1.83 m)

Weight of Unit *(See Page 2 for configuration options and weights)*

Materials High-strength plastic housing
.77 in (19.5 mm) Ultrahigh Molecular Weight Webbing
Forged steel or Aluminum snap hook
Forged Steel or Aluminum rebar hook
Forged Steel or Aluminum carabiner

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength
3,600 lbs (1632 kg) Gate Rated

Maximum Arresting Force <1,800 lbs (816.47 kg)

Maximum Arrest Distance Class B <54 in (137.16 cm)

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)
OSHA up to 420 lbs (190.51 kg)

Webbing Tensile Strength 4,200 lbs (1905.09 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
 322 Industrial Court, Concord, NC 28025

6' Web Personal SRD Series Single Leg Configuration Options

SINGLE	Web Connection				Housing Connection			Material	Weight in lbs. including carabiner			
	Length in Feet	Material	3/4" Steel Snaphook	1.75" Aluminum Snaphook	1.75" Steel Rebar Hook	Housing	No Carabiner			Steel Carabiner	Aluminum Carabiner	
019-5040	6	WEB	X					PLASTIC	X			2.36
019-5041	6	WEB		X				PLASTIC	X			2
019-5042	6	WEB			X			PLASTIC	X			3.35
019-5043	6	WEB				X		PLASTIC	X			2.85
019-5044	6	WEB	X					PLASTIC		X		2.91
019-5045	6	WEB		X				PLASTIC		X		2.55
019-5046	6	WEB			X			PLASTIC		X		3.9
019-5047	6	WEB				X		PLASTIC		X		3.4
019-5048	6	WEB	X					PLASTIC			X	2.69
019-5049	6	WEB		X				PLASTIC			X	2.33
019-5050	6	WEB			X			PLASTIC			X	3.68
019-5051	6	WEB				X		PLASTIC			X	3.18