



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
 322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

7' Web Dual Leg Tie Back SRD Series (20" Tie Back Webbing)

**** Item pictured - Part # 018-5037**



Features and Benefits Safewaze™ 7' Web Dual Leg Tie Back SRD's are designed to be used as a single-person fall protection device. All configurations feature unique clear plastic housings for enhanced unit inspections and a revolutionary internal braking system, which alleviates the need for an external shock pack in such a small, ergonomic SRL. Fall indicators are sewn into webbing.

Length of Web 7 ft (2.13 m) / 20 in length of Tie Back Webbing

Weight of Unit *(See Page 2 for configuration options and weights)*

Materials High-strength clear plastic housings
 .77 in (19.5 mm) Ultrahigh Molecular Weight Webbing
 Steel Tie Back snap hooks

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength
 3,600 lbs (1632 kg) Gate Rated

Maximum Arresting Force <1,800 lbs (816.47 kg)

Maximum Arrest Distance Class A up to 24 in (60.96 cm) if used above Dorsal D-ring
 Class B up to 54 in (137.16 cm) if used up to a maximum of 2 ft below Dorsal D-ring

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)
 OSHA up to 420 lbs (190.51 kg)

Webbing Tensile Strength 4,200 lbs (1905.09 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
 322 Industrial Court, Concord, NC 28025

7' Web Tie Back Series Dual Leg Configuration Options

		Web Connection		Housing Connection											
DUAL	Additional Tie back Length in Feet	3/4" Steel Tie Back Length in Inches	Material	Housing	FS-EX313 Dual Bracket	No Carabiner	Triple Lock Steel Carabiner	Aluminum Carabiner	9013 Behind the Web Bracket	1014 Behind the Web Bracket	Weight in lbs. including carabiner				
	018-5032	7	40	WEB	X	PLASTIC	X	X							5.4
	018-5033	7	40	WEB	X	PLASTIC	X		X						5.95
	018-5034	7	40	WEB	X	PLASTIC	X			X					5.9
	018-5035	7	40	WEB	X	PLASTIC	X				X				5.73
	018-5036	7	40	WEB	X	PLASTIC						X			5.7
	018-5037	7	20	WEB	X	PLASTIC						X			5.65
	019-5136	7	40	WEB	X	PLASTIC							X		5.95
	019-5137	7	20	WEB	X	PLASTIC							X		5.9