



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

SAFEWAZE SAFELINK

019-8034 Bolt on SafeLink Post Baseplate



Description	SAFEWAZE™ Post Baseplate for use with the FS-EX5501-5 SafeLink aluminum post. Can be mounted to concrete or steel. See SafeLink User Manual for installation instructions
Overall Height	12.75 in (323.85 mm)
Base Dimensions	12 in (304.8 mm) x 12 in (304.8 mm)
Attachment Hardware Required	Concrete: (4) 1/2" diameter Anchor Rods with Epoxy (HILTI HIT-Z or similar) 6-1/2" length at a minimum of 4-1/2" embedment in 7 in thick concrete, or (4) 1/2" diameter Concrete Mechanical Anchors (Hilti KWIK HUS or similar) 5" length with a minimum of 4-1/4" embedment in 7 in thick concrete Steel: (4) 1/2" Grade 8 Bolts with locking hardware such as Nyloc Nuts and Flat washers
Material	3/4 in (19.05 mm) Galvanized plate steel
Weight	53 lbs (24.04 kg)
Minimum Breaking Load	5,000 lb (2267.96 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.1 - ANSI A10.32