



[safewaze.com](http://safewaze.com) | (P) 800-230-0319 | (F) 704-262-9051  
 225 Wilshire Ave SW, Concord, NC 28025 USA

## TECHNICAL DATA SHEET

### 020-4020 / 020-4021 Drop Through Anchor



<b>Description</b>	Fall Protection removable / reusable Drop Through Anchor. Easy installation and removal. Must follow installation instructions for proper installation. Suitable for use only on a horizontal surface that is above the users location.
<b>Length</b>	020-4020: <b>2 ft (.61 m)</b> 020-4021: <b>8.5 ft (2.6 m)</b>
<b>Diameter</b>	Minimum Hole Diameter for Installation: 1-3/4 in Maximum Hole Diameter for Installation: 6 in
<b>Materials</b>	Coated Cable Stainless Steel Galvanized Aircraft Cable
<b>Minimum Tensile Strength</b>	5,000 lbs - 22 kN
<b>Weight</b>	020-4020: <b>3.9 lbs (1.77 kg)</b> 020-4021: <b>4.6 lbs (2.09 kg)</b>
<b>Weight Capacity</b>	310 lbs (140.61 kg) - Single user
<b>Applicable Standards</b>	Meets OSHA 1926.502 - OSHA 1910.66 ANSI Z359.1 - ANSI Z359.7

**\*Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.**