



018-5028

Latitude Pro Tie-Back 7' Single Web SRL : No Attachment, 40" Tie-back

FEATURES :

- Class A SRL
- 360/180° attachment point
- 20mm Dyneema® webbing
- Internal brake system
- Semi-sealed pawl assembly
- High strength clear resin housing
- Protective label cover
- No connector
- Steel snap hook
- 40" wear protected tie-back leg providing anchorage connections from 9.5" to 36"

FALL ARREST POINT(S) :

- 1 Tie Back Snap Hook

ITEM WEIGHT :

- 2.5lbs (1.1kg)



USER WEIGHT CAPACITY	
ANSI	130-310lbs (141kg)
OSHA	420lbs (191kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14, A10.32
OSHA	1926.502

HOOK RATING	
Hook Tensile Strength	5,000lbs (2267.96kg)
Hook Gate Rated	5,000lbs (2267.96kg)
CLASS A SRL RATING	
Max Arresting Force	<1,800lbs (816.47kg)
Max Arrest Distance	<24in (609.6mm)

COMPONENT	MATERIAL SPECIFICATION
Housing	Clear Resin
Webbing	20 mm Dyneema®
Wear Pad	Polyester
Lifeline Connector	Steel Tie-Back Snap Hook



018-5029

Latitude Pro Tie-Back 7' Single Web SRL : Carabiner, 40" Tie-back

FEATURES :

- Class A SRL
- 360/180° attachment point
- 20mm Dyneema® webbing
- Internal brake system
- Semi-sealed pawl assembly
- High strength clear resin housing
- Protective label cover
- Steel carabiner connector
- Steel snap hook
- 40" wear protected tie-back leg providing anchorage connections from 9.5" to 36"

FALL ARREST POINT(S) :

- 1 Tie Back Snap Hook
- 1 Carabiner

ITEM WEIGHT :

- 3.1lbs (1.4kg)



USER WEIGHT CAPACITY	
ANSI	130-310lbs (141kg)
OSHA	420lbs (191kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14, A10.32
OSHA	1926.502

HOOK RATING	
Hook Tensile Strength	5,000lbs (2267.96kg)
Hook Gate Rated	5,000lbs (2267.96kg)
Carabiner Tensile Strength	5,000lbs (2267.96kg)
Carabiner Gate Rated	3,600lbs (1632kg)

CLASS A SRL RATING	
Max Arresting Force	<1,800lbs (816.47kg)
Max Arrest Distance	<24in (609.6mm)

COMPONENT	MATERIAL SPECIFICATION
Housing	Clear Resin
Webbing	20 mm Dyneema®
Wear Pad	Polyester
Lifeline Connector	Steel Tie-Back Snap Hook
Housing Connector	Steel Carabiner



018-5030

Latitude Pro Tie-Back 7' Single Web SRL : Triple Lock Carabiner, 40" Tie-back

FEATURES :

- Class A SRL
- 360/180° attachment point
- 20mm Dyneema® webbing
- Internal brake system
- Semi-sealed pawl assembly
- High strength clear resin housing
- Protective label cover
- Steel carabiner connector
- Steel snap hook
- 40" wear protected tie-back leg providing anchorage connections from 9.5" to 36"

FALL ARREST POINT(S) :

- 1 Tie Back Snap Hook
- 1 Carabiner

ITEM WEIGHT :

- 3.1lbs (1.4kg)



USER WEIGHT CAPACITY	
ANSI	130-310lbs (141kg)
OSHA	420lbs (191kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14, A10.32
OSHA	1926.502

HOOK RATING	
Hook Tensile Strength	5,000lbs (2267.96kg)
Hook Gate Rated	5,000lbs (2267.96kg)
Carabiner Tensile Strength	5,000lbs (2267.96kg)
Carabiner Gate Rated	3,600lbs (1632kg)

CLASS A SRL RATING	
Max Arresting Force	<1,800lbs (816.47kg)
Max Arrest Distance	<24in (609.6mm)

COMPONENT	MATERIAL SPECIFICATION
Housing	Clear Resin
Webbing	20 mm Dyneema®
Wear Pad	Polyester
Lifeline Connector	Steel Tie-Back Snap Hook
Housing Connector	Triple Lock Steel Carabiner



018-5031

Latitude Pro Tie-Back 7' Single Web SRL : Alu Carabiner, 40" Tie-back

FEATURES :

- Class A SRL
- 360/180° attachment point
- 20mm Dyneema® webbing
- Internal brake system
- Semi-sealed pawl assembly
- High strength clear resin housing
- Protective label cover
- Steel carabiner connector
- Steel snap hook
- 40" wear protected tie-back leg providing anchorage connections from 9.5" to 36"

FALL ARREST POINT(S) :

- 1 Tie Back Snap Hook
- 1 Carabiner

ITEM WEIGHT :

- 2.8lbs (1.3kg)



USER WEIGHT CAPACITY	
ANSI	130-310lbs (141kg)
OSHA	420lbs (191kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14, A10.32
OSHA	1926.502

HOOK RATING	
Hook Tensile Strength	5,000lbs (2267.96kg)
Hook Gate Rated	5,000lbs (2267.96kg)
Carabiner Tensile Strength	5,000lbs (2267.96kg)
Carabiner Gate Rated	3,600lbs (1632kg)

CLASS A SRL RATING	
Max Arresting Force	<1,800lbs (816.47kg)
Max Arrest Distance	<24in (609.6mm)

COMPONENT	MATERIAL SPECIFICATION
Housing	Clear Resin
Webbing	20 mm Dyneema®
Wear Pad	Polyester
Lifeline Connector	Steel Tie-Back Snap Hook
Housing Connector	Aluminum Carabiner