



# FS-FSP1409-W-DL

Latitude HD 9' Dual Web SRL:  
FS-EX313, Carabiner, Snap Hooks



**Features and Benefits** Reliable internal braking system eliminates the need for external shock pack  
Durable housing and premium webbing increase strength and longevity  
360/180° attachment point offers full range of motion  
Dual hooks to maintain 100% tie-off

**Length of Web** 9 ft (2.7 m)

**Weight of Unit** 6.5 lbs (3 kg)

**Hook Ratings** 5,000 lbs (2267.96 kg) Tensile Strength  
3,600 lbs (1632 kg) Gate Rated

**Maximum Arresting Force** <1,800 lbs (816.47 kg)

**Maximum Arrest Distance** <24 in (609.6 mm)

**Standards Compliant With**

ANSI	Z359.14-14, A10.32
OSHA	1926.502

**ANSI SRL Class** Class A

**User Weight Capacity** ANSI 130-310 lbs (140.6 kg)  
OSHA Up to 420 lbs (190.5 kg)

Material Specifications:	
Webbing	25 mm UHMPE
Lifeline Connectors	Steel Snap Hooks
Housings	Aluminum
Housing Connector	Steel Carabiner



# FS-FSP1409-W-DL-RBH

Latitude HD 9' Dual Web SRL:  
FS-EX313, Carabiner, Rebar Hooks



**Features and Benefits** Reliable internal braking system eliminates the need for external shock pack  
Durable housing and premium webbing increase strength and longevity  
360/180° attachment point offers full range of motion  
Dual hooks to maintain 100% tie-off

**Length of Web** 9 ft (2.7 m)

**Weight of Unit** 8.3 lbs (3.7 kg)

**Hook Ratings** 5,000 lbs (2267.96 kg) Tensile Strength  
3,600 lbs (1632 kg) Gate Rated

**Maximum Arresting Force** <1,800 lbs (816.47 kg)

**Maximum Arrest Distance** <24 in (609.6 mm)

<b>Standards Compliant With</b>	ANSI	Z359.14-14, A10.32
	OSHA	1926.502

**ANSI SRL Class** Class A

**User Weight Capacity** ANSI 130-310 lbs (140.6 kg)  
OSHA Up to 420 lbs (190.5 kg)

<b>Material Specifications:</b>	
Webbing	25 mm UHMPE
Lifeline Connectors	Steel Rebar Hooks
Housings	Aluminum
Housing Connector	Steel Carabiner
FS-EX313 Bracket	Zinc Plated Steel / Aluminum Spacers / Nylon Lock Nuts