



FS-FSP9020

Northstar Classic LE 20' Cable SRL

FEATURES :

- ANSI SRLClass: A/B
- Designed for horizontal, Leading Edge use
- Swivel attachment point
- High-strength polymer housing
- 3/16" galvanized steel cable
- External energy absorber
- Steel carabiner attachment
- Load Indicating swivel snap hook

FALL ARREST POINT(S) :

- 1 Snap Hook
- 1 Carabiner

ITEM WEIGHT :

- 9.8lbs (4.5kg)



USER WEIGHT CAPACITY	
ANSI	130-310lbs (141kg)
OSHA	420lbs (191kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14, A10.32
OSHA	1926.502

HOOK AND CARABINER RATING	
Tensile Strength	5,000lbs (2267.96kg)
Gate Rated	3,600lbs (1632.93kg)
CLASS A SRL RATING (above D-ring)	
Max Arresting Force	<1,8000lbs (816.47kg)
Max Arrest Distance	<24in (609.6mm)
CLASS B SRL RATING (below D-ring)	
Max Arresting Force	<1,8000lbs (816.47kg)
Max Arrest Distance	<54in (1371.6mm)

COMPONENT	MATERIAL SPECIFICATION
Housing	Polymer
Cable	3/16" Galvanized steel
Carabiner	Steel
Snap Hook	Steel



FS-FSP9030

Northstar Classic LE 30' Cable SRL

FEATURES :

- ANSI SRLClass: A/B
- Designed for horizontal, Leading Edge use
- Swivel attachment point
- High-strength polymer housing
- 3/16" galvanized steel cable
- External energy absorber
- Steel carabiner attachment
- Load Indicating swivel snap hook

FALL ARREST POINT(S) :

- 1 Snap Hook
- 1 Carabiner

ITEM WEIGHT :

- 13.7lbs (4.5kg)



USER WEIGHT CAPACITY	
ANSI	130-310lbs (141kg)
OSHA	420lbs (191kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14, A10.32
OSHA	1926.502

HOOK AND CARABINER RATING	
Tensile Strength	5,000lbs (2267.96kg)
Gate Rated	3,600lbs (1632.93kg)
CLASS A SRL RATING (above D-ring)	
Max Arresting Force	<1,8000lbs (816.47kg)
Max Arrest Distance	<24in (609.6mm)
CLASS B SRL RATING (below D-ring)	
Max Arresting Force	<1,8000lbs (816.47kg)
Max Arrest Distance	<54in (1371.6mm)

COMPONENT	MATERIAL SPECIFICATION
Housing	Polymer
Cable	3/16" Galvanized steel
Carabiner	Steel
Snap Hook	Steel



FS-FSP9050

Northstar Classic LE 50' Cable SRL

FEATURES :

- ANSI SRLClass: B/B
- Designed for horizontal, Leading Edge use
- Swivel attachment point
- High-strength polymer housing
- 3/16" galvanized steel cable
- External energy absorber
- Steel carabiner attachment
- Load Indicating swivel snap hook

FALL ARREST POINT(S) :

- 1 Snap Hook
- 1 Carabiner

ITEM WEIGHT :

- 18.6lbs (8.4kg)



USER WEIGHT CAPACITY	
ANSI	130-310lbs (141kg)
OSHA	420lbs (191kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14, A10.32
OSHA	1926.502

HOOK AND CARABINER RATING	
Tensile Strength	5,000lbs (2267.96kg)
Gate Rated	3,600lbs (1632.93kg)
CLASS B SRL RATING (above D-ring)	
Max Arresting Force	<1,8000lbs (816.47kg)
Max Arrest Distance	<54in (1371.6mm)
CLASS B SRL RATING (below D-ring)	
Max Arresting Force	<1,8000lbs (816.47kg)
Max Arrest Distance	<54in (1371.6mm)

COMPONENT	MATERIAL SPECIFICATION
Housing	Polymer
Cable	3/16" Galvanized steel
Carabiner	Steel
Snap Hook	Steel