



FS700-25GA-3E through FS700-100GA-3E

PRO Vertical Lifeline Assembly: Snap Hook, Rope Grab, EA Lanyard

FEATURES :

- 5/8" Polyester rope
- 2 Snap hooks
- Non-removable manual rope grab with dual-cam, and quick locking
- Web energy absorbing lanyard
- Rope tensile strength: 7,500 lbs.
- Hook gate rating: 3,600 lbs.
- Hook minimum breaking strength: 5,000 lbs.

FALL ARREST POINT(S) :

- 2 Snap hooks

ITEM WEIGHT :

- Weight varies by length



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.1-2020, Z359.13-2013
OSHA	1926.502, 1910.66, 1910.140

Size(s)		
FS700-25GA-3E	25 Feet (8 m)	6 lbs. (3 kg)
FS700-50GA-3E	50 Feet (15 m)	9 lbs. (4 kg)
FS700-75GA-3E	75 Feet (23 m)	12 lbs. (5 kg)
FS700-100GA-3E	100 Feet (31 m)	14 lbs. (6 kg)
FS700-150GA-3E	150 Feet (41 m)	19 lbs. (9 kg)

COMPONENT	MATERIAL SPECIFICATION
Rope	Polyester
Snap hooks	Zinc plated alloy steel
Rope grab	Zinc plated alloy steel
Energy absorbing lanyard	Polyester webbing