FS-EX2514

SafeLink Whizzler Swivel Cap

FEATURES:

- · The SafeLink Whizzler Swivel Cap is designed for use with our 7.5' aluminum post
- · Allows a single user increased mobility to work from a stationary anchor point with a 360° degree swivel
- · Allows user to anchor above the dorsal D-ring
- · Use for single-point anchorage applications only
- Length: 16 in. (406 mm)
- · Minimum Breaking Strength: 5,000 lbs.
- Related Parts: FS-EX5501-5 SafeLink Anchor Post, plus a variety of post base options

FALL ARREST POINT(S):

· 1 steel D-ring

ITEM WEIGHT:

• 10.5 lbs (4.8 kg)

| USER WEIGHT CAPACITY | | |
|----------------------|-------------------------|--|
| ANSI | 130-310 lbs. (140.6 kg) | |
| OSHA | N/A | |

| SIZE(S) | | |
|---------|--|--|
| N/A | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| HUX |
|--|
| |
| |
| 3 |
| |
| SAFELINK FS-EX2514 SafeLink Whizzler Swivel Cap |
| The Whitzefan is an discrimination of the following state of the state |
| Section 1 to 1 |
| |

| STANDARD COMPLIANT WITH | | | |
|-------------------------|----------|--|--|
| ANSI | N/A | | |
| OSHA | 1926.502 | | |

| COMPONENT | MATERIAL SPECIFICATION |
|-----------|------------------------|
| Sleeve | Aluminum |
| D-ring | Steel |
| | |
| | |
| | |
| | |
| | |
| | |