



## Latitude Pro 7' Web SRL-P, 20" Tie-Back

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Tie-back convenience when no traditional anchor is available.
- Dependable 5000 lb. rated gate, forged steel tie-back snap hook.
- Reliable internal braking system eliminates need for external shock pack.
- High strength semi-sealed assembly protects internal components from debris to extend product life.
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly.
- 360/180° attachment point offers full range of motion.
- Protective label cover for product longevity and traceability.
- Single leg and dual leg options available.
- Available with various attachment options, see chart.
- All components are Z359.12 compliant.



Class  
**1**  
Anchor at or above dorsal D-ring

Product shown:  
018-5037

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 23 in. (58 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 11 in. (1.8 m)* <small>*Based on full utilization of tie-back leg. For other connections, see manual.</small>
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	*See product manual
Max. free fall distance	*See product manual
Use below d-ring	*See product manual
Min. required fall clearance	*See product manual
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Webbing	20 mm Dyneema® webbing, polyester webbing
Housing	Clear resin
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



## Latitude Pro 7' Web SRL-P, 20" Tie-Back



Standards: ANSI Z359.14-2021  
OSHA 1910.140, 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)  
OSHA Up to 420 lbs. (191kg)

Part Number	Single Leg (S) / Dual Leg (D) SRL Class	Working Length (Ft.)	Lifeline Material	Lifeline Dimensions (In.)	Housing Material	CONNECTOR											ATTACHMENT																	
						Steel Snap Hook (1)	L Steel Swivel Snap Hook (2)	Dinetric Snap Hook (3)	ALU Snap Hook (4)	Steel Tie Back Hook (5)	Steel Rebar Hook (6)	L Steel Swivel Rebar Hook (7)	Steel Swivel Rebar Hook (8)	Steel Rebar Hook (9)	ALU Carabiner Eye Carabiner (10)	ALU Swivel Carabiner (11)	No Attachment	Tip Lock Steel Carabiner (12)	ALU Carabiner (13)	ALU Carabiner (14)	ALU Snap Hook (15)	FS-ER-13 (16)	Cab Mount Bracket (17)	Soft Loop (18)	Integrated DWR (19)	10-4 DWR (20)	9912 DWR (21)	9913 DWR (22)						
018-5037	1	D	7	Dyneema*Webbing	.7X.05	Clear Resin	5.2							X																				X
019-5137	1	D	7	Dyneema*Webbing	.7X.05	Clear Resin	5.4							X																		X		
021-5281	1	S	7	Dyneema*Webbing	.7X.05	Clear Resin	2.8							X											X									

