

# CONCRETE INDUSTRY PRODUCTS

From harnesses and connectors to anchors and positioning devices, Safewaze has the concrete solutions you need, when you need them.



## INSTANT EXPERTISE:

See page 4 to learn more about the ideal conditions to pour concrete

## HARNESSES

### PREMIUM

### VALUE



**PRO+ Slate Construction Harness: Alu 3D, Alu QC Chest, TB Legs**  
020-1190

- › Dorsal SRL link
- › Side positioning D-rings
- › Shoulder and leg pads
- › Aluminum components
- › Quick-connect chest



**PRO+ Full Body Harness: 3D, QC Chest, TB Legs**  
FS-FLEX285

- › Dorsal SRL link
- › Side positioning D-rings
- › Shoulder and leg pads
- › Quick-connect chest



**PRO Construction Harness: 3D, QC Chest, TB Legs**  
FS170-QC

- › Side positioning D-rings
- › Quick-connect chest
- › Shoulder pad
- › Quick-connect chest



**V-Line Full Body Harness: Universal, 1D, QC Chest, TB Legs**  
FS99185-E-QC

- › Quick-connect chest
- › Tongue buckle legs
- › Universal sizing

**LOOK  
INSIDE**



**Dual hooks  
to maintain  
100% tie-off**



## Latitude Pro 7' Dual Web SRL:

- Form Accommodating Rebar Hooks: 019-5139
- Snap Hooks: 018-5016
- 180° / 360° attachment point offers full range of motion
- Reliable internal braking system

## Latitude 6' Dual Web SRL:

- Snap Hooks: 019-5152
- Rebar Hooks: 019-5154
- 180° / 360° attachment point offers full range of motion
- Quick-locking unit designed for use at low heights

## Northstar Classic LE Cable SRL

- 20': FS-FSP9020
- 30': FS-FSP9030
- 50': FS-FSP9050
- Enhanced swivel top for greater mobility



## Northstar Classic 20' Cable SRL

- FS-FSP1220-G
- Load indicating snap hook easily identifies when product has arrested a fall



## Chain Assembly: Swivel Rebar Hook

- 19": FS061
- 26": FS060
- Flexible, adjustable method to position a user in a full-body harness for work positioning applications



## PRO 4'-6' Adjustable Energy Absorbing Lanyard: Rebar Hook

- FS565-AJ
- UV and abrasion resistant hi-vis green webbing



## Leading Edge 6' Energy Absorbing Lanyard: Dual Leg, Alu Swivel Rebar Hooks

- 019-2016
- 2 swivel aluminum rebar hooks



# ANCHORS



**5K Swivel Anchor & Concrete Wedge Bolt**

021-4054

- 180° / 360° rotating connection point for increased mobility



**5K Swivel D-ring Anchor Assembly**

021-4081

- Used vertically or horizontally



**5K Removable Concrete Hole Anchor**

FS876

- Removable and reusable



**Cable Choker Anchor**

FS830

- Ideal for small-diameter anchorage situations



**Concrete Anchor Strap: Soft Loop**

70180

- Constructed with heavy duty webbing with wear sleeve
- Soft webbing loops at each end



**Reinforced Cross Arm Strap**

FS810

- Constructed with heavy duty webbing with wear sleeve
- 2 forged steel D-rings



**Concrete Anchor Strap**

FS880

- Constructed with heavy duty webbing with wear sleeve
- Loop attachment end slips over rebar for easy installation



**Ratchet Anchor Strap**

FS-EX400-15

- Lightweight and portable, easy install





# SAFEWAZE



## ACCESSORIES



### Small Steel Carabiner

FS1015

- 3,600 lbs. twist lock gate
- Gate opening 0.75"



### Steel Boa Carabiner w/Captive Pin

FS1017

- 3,600 lbs. twist lock gate
- Large gate opening 2"



### Suspension Trauma Steps

FS902

- Quickly attaches to most harnesses



### 18" D-ring Extender: Rebar Hook, D-ring

FS814

- Provides additional length between the harness dorsal D-ring and connection



### STAT

Pouring concrete in too hot or cold weather can effect the curing process. Hot weather can reduce the amount of water in the mixture. Cold weather makes the curing process take much longer; slow curing concrete can shift over time and cause damage. The ideal temperature to pour concrete is 50° to 60° Fahrenheit. This can be as early as March depending on your location. Plan accordingly for the warm weather rush.



225 Wilshire Avenue SW, Concord NC 28025



800-230-031



[safewaze.com](http://safewaze.com)

