

SAFEWAZE TECHNICAL DATA SHEET

022-11033 10' Tech Tripod Complete

FEATURES :

- Lightweight aluminum construction
- Quick setup with easy height and diameter adjustment using detent pins
- Multiple stance configurations to allow for a variety of work zones, including an over-anedge scenario
- 7 Individual 5,000 lb. anchor points in the head unit including a centered 360° captive eye
- · Multi-surface steel feet with rubber pads
- 2 Removable and adjustable steel steps with detent pins for easier access to anchor points
- Perimeter warning line with brackets for prevention of fall hazards
- Safety chain and quick link
- Convenient and durable storage/travel bag
- Min. Breaking Strength: 5,000 lbs. (2268 kg)
- Maximum Material Capacity: 620 lbs. (281 kg)
- System Capacity: 620 lbs. (281 kg)

FALL ARREST POINT(S) :

- 360° Captive Eye
- (6) 5,000 lb. Anchor Points in Head Unit

ITEM WEIGHT :

• 70. 0 lbs. (31.8 kg)

| USER WEIGHT CAPACITY | | |
|----------------------|--------------------------|--|
| ANSI | 130-310 lbs. (59-141 kg) | |
| OSHA | Up to 420 lbs. (191 kg) | |

| COMPATIBLE COMPONENTS | | |
|-----------------------|--------------------------|--|
| 019-11010 | Universal Tripod Bracket | |
| 019-11017 | Tripod Replacement Chain | |
| 022-11031 | Perimeter Warning Line | |
| 022-11030 | Tripod Step | |
| 020-11025 | Aluminum Pulley | |
| | | |
| | | |
| | | |
| | | |



| STANDARD COMPLIANT WITH | | |
|-------------------------|---|--|
| ANSI | Z359.18-2017 Type T, Z359.4-2013, Z117.1-2022 | |
| OSHA | 1926.502, 1910.140 | |

| COMPONENT | MATERIAL SPECIFICATION |
|------------------------|-------------------------------------|
| Tripod Base/Legs | Aluminum |
| Head Unit | Aluminum |
| Captive Eye | Stainless Steel |
| Feet | Powder coated steel, rubber |
| Fasteners | Zinc plated steel |
| Detent Pins | Nylon/Stainless steel |
| Steps | Powder coated steel |
| Perimeter Warning Line | Polyester, zinc plated steel, nylon |