



023-4095

Standing Seam SRL Swivel Anchor

FEATURES :

- Reusable non-penetrating anchor point
- Designed for flat or pitched standing seam roofs with a minimum gauge 26
- Equipped with (6) S-5-U clamps for attachment onto a variety of standing seam profiles
- Adjustable crossarm spans 24-40" and locks with detent pins
- 360° swivel base for increased user mobility
- Smart cradle design accommodates most SRL sizes with quick carabiner attachment to the anchor post
- D-ring connection point for energy absorbing lanyards, VLLs and HLLs
- Minimum Breaking Strength: 3,600 lbs. (16 kN)
- 1 user maximum as single point anchor, 2 user maximum per span for HLLs

FALL ARREST POINT(S) :

- D-ring for lanyards, VLLs and HLLs
- Anchor post for SRLs (no disassembly required)

ITEM WEIGHT :

- 29.4 lbs. (13.3 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	n/a
OSHA	1926.502, 1910.140, 1910.66

RELATED PRODUCTS	
023-4096	Standing Seam Swivel Anchor
023-4101	S-5-U Clamp

COMPONENT	MATERIAL SPECIFICATION
Anchor	Powder coated steel, stainless steel
S-5-U Clamps	Aluminum