



019-4005

FrogLink Temporary Roof Anchor

FEATURES :

- Can be used as a single point anchor or as part of a horizontal lifeline system
- 360° working radius
- Built-in energy absorber reduces stress or damage to the mounting structure
- Easily attaches with (7) 14 gauge 75 mm long roofing screws (not included)

LENGTH:

- 8.5 in. (216 mm)

MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

FALL ARREST POINT(S) :

- 1 Formed Loop

ITEM WEIGHT :

- .6 lbs. (.3 kg)



| USER WEIGHT CAPACITY | |
|----------------------|--------------------------|
| ANSI | 130-310 lbs. (59-141 kg) |
| OSHA | Up to 420 lbs. (191 kg) |

| STANDARD COMPLIANT WITH | |
|-------------------------|-----------------------------|
| ANSI | Z359.18-2017 Type D |
| OSHA | 1926.502, 1910.140, 1910.66 |

| SIZE(S) | |
|---------|--|
| N/A | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| COMPONENT | MATERIAL SPECIFICATION |
|-----------|------------------------|
| Anchor | Stainless Steel |
| | |
| | |
| | |
| | |
| | |
| | |
| | |