



Scaffold Davit Anchor (see chart below for SKUs)

FEATURES:

- Versatile anchor point that clamps directly to vertical, supported scaffolding with the following diameter ranges:
 - **023-4104:** 1.6"-2" (40.6 mm - 50.8 mm)
 - **024-4119:** 2.25"-2.75" (57.2 mm - 69.9 mm)
 - **024-4120:** 2.5"-3" (63.5 mm - 76.2 mm)
- Scaffolding must extend at least 6" (152.4 mm) past each scaffold clamp
- Horizontal pivoting and locking system allows for optimum positioning, reducing swing fall risk

MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

ITEM DIMENSIONS:

- 40" x 18" x 2.4" (1016 mm x 457.2 mm x 61 mm)

ITEM WEIGHT:

- 32 lbs. (14.5 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.18-2017 Type A
OSHA	1926.502, 1910.140, 1910.66

SIZE(S):	
023-4104	1.6"-2" (40.6 mm - 50.8 mm)
024-4119	2.25"-2.75" (57.2 mm - 69.9 mm)
024-4120	2.5"-3" (63.5 mm - 76.2 mm)

COMPONENT	MATERIAL SPECIFICATION
Anchor Base	Powder-coated steel
Captive Eyes	Zinc-plated steel
Clamps	Zinc-plated steel