



## FS871-25

### Knock-Down Roof Anchor: Pack 25

#### FEATURES :

- Knockdown, disposable design
- Installs on pitched wood roofs
- Anchor can be shaped by hand to conform to different roof contours
- Not for permanent use, not reusable
- Not for HLL use
- Minimum breaking strength: 3,600 lbs. (16 kN)
- Size: 10" x 6" x 2.25" (25.4 x 15.2 x 5.7cm)
- Fasteners not included with FS871
- (8) 16D roofing nails are included with FS871N
- Also available in pack of 25: FS871-25

#### FALL ARREST POINT(S) :

- 1 formed dual layer eyelet

#### ITEM WEIGHT :

- 0.8 lbs. (0.4 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (140.6 kg)
OSHA	N/A

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

RELATED PRODUCTS	
FS871N	Knock-Down Roof Anchor, 8pc Nails
021-4067	8pc 16D Roofing Nails for FS871
FS871N-25	Knock-Down Roof Anchor: 25 Anchors, 200 Nails

COMPONENT	MATERIAL SPECIFICATION
Anchor	Zinc plated steel
Nails (FS871N-25)	Plated steel
Nails (FS871N)	Plated steel