



024-1478-1485

PRO+ Slate Tower Construction Harness:

Alu 3D, Alu QC Chest, Alu FD, TB Legs, Tower Seat

FEATURES:

- Lightweight aluminum construction harness
- Equipped with 2 additional aluminum D-rings for positioning and suspension
- Aluminum dorsal D-ring
- Aluminum front-sternal D-ring
- Aluminum quick torso adjusters
- Aluminum quick-connect chest
- Tongue buckle legs
- Shoulder pad
- Fixed comfort waist pad
- Removable leg pads
- Tower seat included, but also sold separately
- Padded tower seat is removable and adjustable
- Two additional tool rings included on tower seat

FALL ARREST POINT(S):

- 1 Dorsal D-ring
- 1 Integrated SRL Channel

ITEM WEIGHT:

- With seat: 10.1 lbs. (4.6 kg)
- Without seat: 6.8 lbs. (3.1 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
024-1478	X-Small
024-1479	Small
024-1480	Medium
024-1481	Large
024-1482	X-Large
024-1483	2X
024-1484	3X
024-1485	4X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring(s)	Aluminum
Adjuster buckles	Aluminum
Chest connection	Aluminum
Leg connection	Steel tongue buckle w/ SS grommets
Dorsal SRL link	Polyester
O-rings	Zinc-plated steel
Pads	Nubuck synthetic; Spandex; Poly mesh; EVA
Belt	Polyester; Steel; Stainless steel
Seat	Aluminum; Polyester; EVA; Steel; Plastic