



## FS830-C3-2

## Cable Sling Anchor: Snap Hook

### FEATURES:

- Lightweight and portable
- Easy to install
- 2 steel O-rings for anchor and connection points
- PVC coated 5/16" steel cable
- Available in a variety of lengths

### MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

### ATTACHMENT POINT(S):

- 2 O-rings
- 1 Snap hook

### ITEM WEIGHT:

- Varies by length (see chart below)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.18-2017 Type T
OSHA	1910.140, 1926.502, 1910.66

SIZES/WEIGHTS	
FS830-C3-2 (3')	2 lbs. (0.9 kg)
FS830-C6-2 (6')	2.3 lbs. (1 kg)
FS830-C8-2 (8')	2.5 lbs. (1.1 kg)
FS830-C10-2 (10')	2.7 lbs. (1.2 kg)

COMPONENT	MATERIAL SPECIFICATION
Cable	PVC-coated galvanized steel
Thimble	Zinc-plated steel
Ferrule	Aluminum
O-rings	Zinc-plated steel
Snap Hook	Zinc-plated steel