



FS88860

6' Web Restraint Lanyard

FEATURES :

- Non-energy absorbing connector for use in restraint applications
- 1" hi-vis green webbing
- 2 forged steel snap hook
- Minimum Breaking Strength: 5,000 lbs.
- All components are ANSI Z359.12 Compliant

ATTACHMENT POINT(S) :

- 2 Snap Hook

ITEM LENGTH :

- Length varies (see size chart below)

ITEM WEIGHT :

- Varies per length (see size chart below)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.3-2019
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)	
FS88860	6 ft. (1.8 m)
FS88860-2	2 ft. (0.6 m)
FS88860-3	3 ft. (0.9 m)
FS88860-4	4 ft. (1.2 m)
FS88860-8	8 ft. (2.4 m)

COMPONENT	MATERIAL SPECIFICATION
Webbing	1" Polyester
Snap Hook	Forged zinc plated steel



Serie FS88860

Acollador tejido de restricción

CARACTERÍSTICAS:

- Conector sin absorción de energía para usos de restricción
- Tejido verde de alta visibilidad 1"
- 2 ganchos autocierre de acero forjado
- Todos los componentes cumplen con las pautas de ANSI Z359.12.

RESISTENCIA MÍNIMA A LA ROTURA:

- 5,000 lb (22 kN)

PUNTOS DE ENGANCHE:

- 2 gancho autocierre

LONGITUD DEL ARTÍCULO:

- Varía (consulte la tabla de talles que figura abajo)

PESO DEL ARTÍCULO:

- Varía según la longitud (consulte la tabla de talles que figura abajo)



CAPACIDAD DE PESO DEL USUARIO	
ANSI	De 130 a 310 lb (entre 59 y 141 kg)
OSHA	Hasta 420 lb (191 kg)

NORMAS CUMPLIDAS	
ANSI	Z359.3-2019
OSHA	1926.502, 1910.140, 1910.66

TALLES	
FS88860	6' (1.8 m): 2.8 lb (1.3 kg)
FS88860-2	2' (0.6 m): 2.5 lb (1.1 kg)
FS88860-3	3' (0.9 m): 2.6 lb (1.2 kg)
FS88860-4	4' (1.2 m): 2.7 lb (1.2 kg)
FS88860-8	8' (2.4 m): 2.9 lb (1.3 kg)

COMPONENTE	ESPECIFICACIÓN DEL MATERIAL
Tejido	Poliéster 1"
Gancho autocierre	Acero cincado forjado