



023-4108

Toggle Anchor

FEATURES:

- For metal or hollow core concrete structures
- Used horizontally or vertically
- Requires 3/4" predrilled hole for installation
 - Installs into steel substrate with 1/4 to 3" thickness
 - Installs into hollow core concrete 5000 PSI or higher with minimum 6" thickness and 1-3/4" to 3" web thickness
- Indicator wire to visually confirm proper installation
- Suited for use with all PFAS including HLLs

DIMENSIONS:

- 11" x 1-1/4" x 1-1/4"

ATTACHMENT POINT(S):

- 1 Anchor loop

MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

WORKING LOAD LIMIT:

- 1,000 lbs. (4.4 kN)

ITEM WEIGHT:

- 0.6 lbs. (0.3 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.18-2017 Type A
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)	
N/A	

COMPONENT	MATERIAL SPECIFICATION
Hole plug	Aluminum
Spring	Stainless steel
Toggle bar	Stainless steel
Loop cover	Polyurethane
Cable	Galvanized steel
Label cover	Polyester and tarpaulin