



024-11042

65' 3-Way System, Universal Mount - Xtirpa Mounting Capable

FEATURES:

- Serves as the support element, provides fall protection and facilitates rescue or evacuation if necessary
- Storable handle, max operation force: 30 lbs. (13.6 kg)
- 6:1 gear ratio
- Carrying handle
- Universal mounting bracket
- Universal Tripod Bracket (019-11010) is required for installation (not included)
- All components are Z359.12 compliant
- Capable of being mounted to most Xtirpa products

MINIMUM BREAKING STRENGTH:

- 3,600 lbs. (16 kN)

FALL ARREST POINT(S):

- 1 snap hook

ITEM WEIGHT:

- 36.2 lbs. (16.4 kg)



Class
1
Anchor at or above
dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021, Z359.4-2013
OSHA	1926.502, 1910.66, 1910.140

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 28 in. (71 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	5 ft. 10 in. (1.8 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Aluminum
Handle	Steel with plastic grip
Mounting bracket	Zinc-plated steel
Cable	3/16" galvanized steel
Load indicating swivel snap hook	YCM plated steel