



Latitude Edge Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Lightweight, durable housing design
- Exclusive dorsal attachment bracket with SRL separator feature.
- Compact shock pack design with harness restraint strap.
- 360/180° attachment point offers full range of motion.
- Side payout for smooth retraction.
- Exclusive edge resistant engineered composite webbing.
- Protective label cover for product longevity and traceability.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class
2
Anchor above or below dorsal D-ring

Product shown:
023-5344

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 11 in. (2.1 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 76 in. (193 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	14 ft. 10 in. (4.5 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Web	Specialized composite
Bracket	Stainless steel, steel and aluminum
Housing	Nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester

