



021-7019 through 021-7021 PRO Kernmantle Vertical Lifeline

FEATURES:

- Available in lengths from 30'-100'
- 7/16" (11mm) black Kernmantle rope with green tracers
- Durable, impact-resistant captive eye termination with swivel snap hook on one end and sewn termination on other end
- Rope tensile strength: 8,200 lbs. (36.5 kN)
- Rope elongation: 6% at 1,800 lbs. (8 kN)
- *To be a compliant ANSI Z359.15 system, lifeline must be used in conjunction with a compatible and approved fall arrester with energy absorbing lanyard. See user manual for additional restrictions and specifications.

FALL ARREST POINT(S):

- 1 Swivel snap hook

ITEM WEIGHT:

- Weight varies per length



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	N/A

STANDARD COMPLIANT WITH	
ANSI	Z359.15-2014*
OSHA	1926.502, 1910.66, 1910.140

SIZE(S)		
021-7019	30 feet (9 m)	3.0 lbs. (1.4 kg)
021-7020	50 feet (15 m)	4.4 lbs. (2.0 kg)
021-7021	100 feet (30 m)	7.9 lbs. (3.6 kg)

COMPONENT	MATERIAL SPECIFICATION
Kernmantle rope	Polyester
Swivel snap hook	Zinc-plated steel
Termination	Stainless steel, plastic shrink tube