



## 022-7025

### Drift 7/16" (11 mm) Rope Fall Arrester

#### FEATURES:

- Lightweight aluminum design with high grade 7075 aluminum housing
- Wear resistant Zytel® nylon rollers
- Stainless steel internal components
- Visual indicators for upright installation
- Ergonomically placed mode control switch
- Flared housing for pinch free use and reduced rope friction
- Double locking gate
- Connect and disconnect with one hand without removing carabiner
- Includes backup anchor descent cord for use in rescue scenarios
- Use with 7/16" (11 mm) rope
- Minimum Breaking Strength: 3,600 lbs. (16 kN)

\*To be a compliant ANSI Z359.15-2014 system, the fall arrester must be used in conjunction with a compatible and approved vertical lifeline with energy absorbing lanyard. See user manual for additional specifications

#### FALL ARREST POINT(S):

- N/A

#### ITEM WEIGHT:

- 0.7 lbs. (0.3 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	N/A

STANDARD COMPLIANT WITH	
ANSI	Z359.15-2014*
OSHA	1926.502, 1910.66, 1910.140

SIZE(S)	
N/A	

COMPONENT	MATERIAL SPECIFICATION
Rope grab	Anodized aluminum, stainless steel, nylon
Cord	2.5 mm nylon