



024-2152

Arc Flash 6' Internal Energy Absorbing Lanyard: Aramid, Soft Loop, Rebar Hook

FEATURES:

- 1-3/8" tubular aramid webbing with internal energy absorber
- 1 forged steel rebar hook
- 1 aramid soft loop
- Nomex® label cover
- Single leg construction
- 40Cal/750F rated
- All components are ANSI Z359.12 Compliant

MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

ATTACHMENT POINT(S):

- 1 Rebar hook
- 1 Soft loop

ITEM LENGTH:

- 6' (1.8 m)

ITEM WEIGHT:

- 2.6 lbs. (1.2 kg)



| USER WEIGHT CAPACITY | |
|----------------------|--------------------------|
| ANSI | 130-310 lbs. (59-141 kg) |
| OSHA | N/A |

| STANDARD COMPLIANT WITH | |
|-------------------------|-----------------------------|
| ANSI | Z359.13-2013 |
| OSHA | 1926.502, 1910.140, 1910.66 |
| ASTM | F887 |

| SIZE(S) | |
|---------|--|
| N/A | |
| | |
| | |
| | |
| | |
| | |

| COMPONENT | MATERIAL SPECIFICATION |
|-------------|------------------------|
| Webbing | 1-3/8 aramid |
| Rebar hook | Zinc-plated steel |
| Label cover | Nomex® |
| | |
| | |
| | |