



Latitude Edge Tie-Back Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Lightweight, durable housing design
- Exclusive dorsal attachment bracket with SRL separator feature.
- Compact shock pack design with harness restraint strap.
- 360/180° attachment point offers full range of motion.
- Side payout for smooth retraction.
- Exclusive edge resistant engineered composite webbing.
- Protective label cover for product longevity and traceability.
- Single leg and dual leg options available.
- 20" or 40" extension with tie-back snap hook for wrapping around your anchor point.
- All components are Z359.12 compliant.



Class

2

Anchor above or below dorsal D-ring

Product shown:
024-5402

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 11 in. (2.1 m)* <small>*Based on full utilization of tie-back leg. For other connections, see manual.</small>
For full clearance requirements, see user instructions	

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	*See product manual
Max. free fall distance	*See product manual
Min. required fall clearance	*See product manual
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Web	Proprietary composite webbing
Bracket	Steel and aluminum
Housing	Nylon
Hook options	Zinc-plated steel
Shock pack	Polyester



Latitude Edge Tie-Back Web SRL-P



Standards: ANSI Z359.14-2021
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Straps (S) / Dual Leg (D)	Working Length (ft)	Lifeline Material	Lifeline Dimensions (in)	Housing Material	Weight (lbs)	U-Steel Swivel Snap Hook ①	U-Steel Swivel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	Steel Rebar Hook ⑤	Steel Sawtooth Rebar Hook ⑥	Steel Sawtooth Rebar Hook ⑦	Steel Sawtooth Rebar Hook ⑧	Steel Carabiner Eye Carabiner ⑨	AlU Rebar Hook ⑩	AlU Carabiner Eye Carabiner ⑪	AlU Swivel Carabiner ⑫	No Attachment	Steel Carabiner ⑬	Tip Lock Steel Carabiner ⑭	AlU Carabiner Eye Carabiner ⑮	AlU Carabiner ⑯	AlU Snap Hook ⑰	ES-2313 ⑱	Carb Mount Impact ⑲	Soft Loop ⑳	Integrated BHB ㉑	1.0" x BHB ㉒	30.1" BWS ㉓	30.1" BWS ㉔				
024-5402	2 S	8	Composite	1x.35	Nylon	4.9	X					X																							
024-5403	2 D	8	Composite	1x.35	Nylon	8.5						X																							
024-5404	2 S	8	Composite	1x.35	Nylon	5.0						X																							
024-5405	2 D	8	Composite	1x.35	Nylon	9.7						X																							

