



024-1379-1381

Arc Flash Wind & Tower Harness: 5D, QC Legs

FEATURES:

- Step-in style construction
- Dielectric dorsal D-ring
- Dielectric front-sternal D-ring
- Dielectric front-waist d-ring
- Dielectric side D-rings
- Alu quick torso adjusters
- Dielectric quick-connect chest
- Dielectric quick-connect legs
- Alu carabiner front connection
- Component backers
- Adjustable rear leg straps
- Kevlar® tool loops
- Nomex® and Kevlar® shoulder, waist, and removable leg pads
- 40Cal/700F rated aramid webbing

FALL ARREST POINT(S):

- 1 Dorsal d-ring

ITEM WEIGHT:

- 7.2 lbs. (3.3 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140
ASTM	F887

SIZE(S)	
024-1379	Small/Medium
024-1380	Large/X-Large
024-1381	2X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Aramid and nylon
D-ring(s)	Dielectric steel
Quick Connects	Dielectric steel
Mating buckle(s)	Dielectric steel
Adjuster buckle(s)	Aluminum
Carabiner(s)	Aluminum
O-rings	Zinc-plated steel
Pads	Nomex® and Kevlar®
Tool Loops	Kevlar®