



024-1385-1387

Arc Flash Wind & Tower Harness: 5D, Removable Seat, QC Legs

FEATURES:

- Step-in style construction
- Dielectric dorsal D-ring
- Dielectric front-sternal D-ring
- Dielectric front-waist d-ring
- Dielectric side D-rings
- Alu quick torso adjusters
- Dielectric quick-connect chest
- Dielectric quick-connect legs
- Alu carabiner front connection
- Component backers
- Adjustable rear leg straps
- Kevlar® tool loops
- Nomex® and Kevlar® shoulder, waist, and removable leg pads
- Removable positioning/suspension seat
- 40Cal/700F rated aramid webbing

FALL ARREST POINT(S):

- 1 Dorsal D-ring

ITEM WEIGHT:

- 10.4 lbs. (4.7 kg)



| USER WEIGHT CAPACITY | |
|----------------------|--------------------------|
| ANSI | 130-310 lbs. (59-141 kg) |
| OSHA | Up to 420 lbs. (191 kg) |

| STANDARD COMPLIANT WITH | |
|-------------------------|--------------------|
| ANSI | Z359.11-2021 |
| OSHA | 1926.502, 1910.140 |
| ASTM | F887 |

| SIZE(S) | |
|----------|---------------|
| 024-1385 | Small/Medium |
| 024-1386 | Large/X-Large |
| 024-1387 | 2X |
| | |
| | |
| | |
| | |
| | |
| | |

| COMPONENT | MATERIAL SPECIFICATION |
|--------------------|------------------------|
| Webbing | Aramid and nylon |
| D-ring(s) | Dielectric steel |
| Quick Connects | Dielectric steel |
| Mating buckle(s) | Dielectric steel |
| Adjuster buckle(s) | Aluminum |
| Carabiner(s) | Aluminum |
| O-rings | Zinc-plated steel |
| Pads | Nomex® and Kevlar® |
| Tool Loops | Kevlar® |