



024-4112

Corrugated Roof Anchor: Steel

FEATURES:

- Designed for use on corrugated roofs with maximum ridge height of 1-3/4" and maximum rive width of 3-3/4"
- 360° rotating swivel D-ring
- Requires (6) #12 or #14 metal-to-metal self-drill HWH screws with integrated EPDM washers. Length of screw is dependent on the roof gauge, purlin thickness, and anchor depth of 1/8". Minimum embedment of 1/4" into purlin is required.
- Minimum valley spacing of 8" between ridges
- Temporary and reusable
- Not suitable for Horizontal Lifeline (HLL) or material hauling use.
- Dimensions: 20.1" x 4" x 2.9" (510 mm x 101.5 mm x 74 mm)

ATTACHMENT POINT(S):

- 1 D-ring

MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

ITEM WEIGHT:

- 4.8 lbs. (2.2 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)	
N/A	

COMPONENT	MATERIAL SPECIFICATION
Anchor base	Zinc-plated steel
D-ring	Zinc-plated steel