



## Northstar Classic Stainless Steel Cable SRL

\*See chart for additional part numbers, hook configurations, and product weights

### FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class  
**1**  
Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 36 in. (91 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 6 in. (2.0 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Stainless steel



## Northstar Classic Stainless Steel Cable SRL

Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	L Steel Swivel Snap Hook ①	Steel Snap Hook ②	L Steel Swivel Snap Hook ③	Dielectric Snap Hook ④	Steel Tie Back Hook ⑤	L Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	Steel Swivel Rebar Hook ⑧	Steel Captive Eye Carabiner ⑨	ALU Captive Eye Carabiner ⑩	ALU Swivel Carabiner ⑪	No Attachment	Trip Lock Steel Carabiner ⑬	ALU Captive Eye Carabiner ⑭	ALU Carabiner ⑮	ALU Snap Hook ⑰	Cab Mount Bracket FS-EX133 ⑱	Soft Loop ⑲	Integrated DWB ⑳	1014 B/WB ㉑	9012 B/WB ㉒	9013 B/WB ㉓	
FS-FSP1420-W	1 S	20	UHMPE Webbing	1X.05	Polymer	5.9	X												X										
FS-FSP1215-G	1 S	15	Steel Cable	ø3/16	Polymer	6.7		X											X										
FS-FSP1215-SS	1 S	15	S.S. Cable	ø3/16	Polymer	6.7		X											X										
FS-FSP1220-G	1 S	20	Steel Cable	ø3/16	Polymer	7.9		X											X										
FS-FSP1220-SS	1 S	20	S.S. Cable	ø3/16	Polymer	7.9		X											X										
FS-FSP1230-G	1 S	30	Steel Cable	ø3/16	Polymer	10.1		X											X										
FS-FSP1230-SS	1 S	30	S.S. Cable	ø3/16	Polymer	10.1		X											X										
FS-FSP1250-G	1 S	50	Steel Cable	ø3/16	Polymer	15.2		X											X										
FS-FSP1250-SS	1 S	50	S.S. Cable	ø3/16	Polymer	15.2		X											X										
FS-FSP1265-G	1 S	65	Steel Cable	ø3/16	Polymer	20.4		X											X										
FS-EX1080-G	1 S	80	Steel Cable	ø3/16	Polymer	27.4		X											X										
FS-EX10-100-G	1 S	100	Steel Cable	ø3/16	Polymer	30.4		X											X										

