





SMOOTH TRAILING FOR MORE FREEDOM OF MOVEMENT

SLIDING BEAM ANCHORS

ENGINEERED FOR EFFICIENCY

- Hands-free mobility
- Lightweight & compact
- One-handed trigger action
- Dual adjustment





It's Smooth Trailing With These Sliding Beam Anchors.

The Increased Range Of Movement Increases Job Efficiency.



BEAM WALKER EASY SLIDER

PREMIER SLIDING BEAM ANCHOR

SHARED FEATURES of sliding beam anchors

- Smooth trailing action follows user for hands-free mobility
- Lightweight aluminum construction with steel D-rings
- Easy, one-handed lock & release trigger action
- Temporary, portable anchor rugged enough for repeated use



(beam anchor shared features continued)

- Two adjustable jaws for quick installation
- Versatile use with overhead or foot level tie-off
- Extended OSHA weight capacity up to 420 lbs.
- Protective cover keeps labels in compliance

UNIQUE FEATURES

- 180° ROTATING D-RING: Pivots for greater mobility
- NYLON ROLLERS: Increased slide efficiency
- REPLACEMENT JAW LINERS: Save money, extend anchor life and restore original slide functionality



UNIQUE FEATURES

• 180°/360° SWIVEL D-RING: Rotates fully in all directions for maximum mobility

• **PERMANENT JAW LINERS:** Reinforced jaws for sturdy yet smooth sliding action









Anchor





800-230-0319 • safewaze.com

225 Wilshire Avenue SW

Concord NC 28025



SLIDING BEAM ANCHORS

Lightweight anchor points with hands-free mobility designed for easy attachment to I-beams and other structural components.

	021-4055	Premier Sliding Beam Anchor	Overall Length: 19.5" Beam Flange Width Range: 4"-13" Beam Flange Thickness: Up to 1.25"
	021-4068	Beam Walker Easy Slider 3.5"-14"	Overall Length: 19.5" Beam Flange Width Range: 3.5"-14" Beam Flange Thickness: Up to 1.25"
ft · · j	021-4069	Beam Walker Easy Slider 12"-30"	Overall Length: 37" Beam Flange Width Range: 12"-30" Beam Flange Thickness: Up to 2.6"
	021-4075	Sliding Beam Anchor 3.5"-15"	Overall Length: 20.5" Beam Flange Width Range: 3.5"-15" Beam Flange Thickness: Up to 1.25"
	018-4001	Beam Trolley Anchor	Beam Flange Width Range: 3.5"-14" Beam Flange Thickness: Up to 1.75"
	019-4009	Vertical/Stationary Beam Anchor 3.5"-14"	Beam Flange Width Range: 3.5"-14"

FROM ANCHORS, BODYWEAR AND CONNECTORS TO DESCENT AND RESCUE, WE'VE GOT THE EXACT FALL PROTECTION YOU NEED.

