



024-2142

PRO-Shield 6' Energy Absorbing Lanyard: Dual Leg, Rebar Hooks

FEATURES :

- 1" Polyurethane coated webbing for water and chemical resistance (see back for more information)
- Dual leg construction
- 1 Forged steel snap hook
- 2 Forged steel rebar hooks
- Easy to clean with increased durability
- Rubberized, water repellent shock pack with label cover
- Minimum Breaking Strength: 5,000 lbs.
- All components are ANSI Z359.12 compliant

ATTACHMENT POINT(S) :

- 1 Snap hook
- 2 Rebar hooks

ITEM LENGTH :

- 6' (1.8 m)

ITEM WEIGHT :

- 5.4 lbs. (2.5 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	N/A

STANDARD COMPLIANT WITH

ANSI	Z359.13-2013
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)

COMPONENT

MATERIAL SPECIFICATION

Webbing	Polyurethane coated polyester
Rebar hooks	Zinc-plated steel
Snap hook	Zinc-plated steel
Label cover	Rubberized synthetic
D-ring	Zinc-plated steel

**CHEMICAL RESISTANCE RATING**

RATING SCALE	
EXCELLENT - Little or no change	5
GOOD - Slight loss in properties, slight swell	4
FAIR - Some loss in properties, swelling	3
POOR - Significant loss of properties, significant swelling	2
DISSOLVES - Not recommended	1

ACIDS	RATING	ORGANICS (CONT.)	RATING
ACETIC, 5%	4	DIOCTYL PHTHALATE	3
FORMIC, 20%	2	ETHYL ETHER	3-4
HYDROCHLORIC, 10%	3	ETHYLENEN GLYCOL	4
OLEIC	3-4	ETHYLENEN GLYCOL, 50% H2O	4
SULFURIC, 20%	3	GASOLINE, 100 OCTANE	3
		HEXANE	3-4
ALCOHOLS		KEROSENE	4
ETHANOL	2	METHYLENE CHLORIDE	2
ISOPROPANOL	2-3	METHYL ETHYL KETONE	2
ISOPROPANOL, 50%	2-3	N-NETHYL-2-PYRROLIDENE	1
METHANOL	2	OIL, TEXAS CRUDE	3-4
		OIL, DETERGENT 20W	4
ALKALI		OIL, NONDETERGENT 20W	4
SODIUM HYDROXIDE, 20%	3	OIL, SKYDROL TYPE B	1
		OIL, SKYDROL TYPE 500A	2-3
ORGANICS		OIL, SKYDROL TYPE 500B	2-3
ACETONE	2	OIL, TRANSMISSION TYPE A	4
ASTM FUEL A	4	PERCHLOROETHYLENE	2
ASTM FUEL B	3	PYRIDINE	1
ASTM FUEL C	2-3	TETRAHYDROFURAN	1
ASTM OIL #1	4	TOLUENE	2
ASTM OIL #2	4	TRICHLOROETHYLENE	2
ASTM OIL #3	3-4	TURPENTINE	4
BENZENE	2		
BRAKE FLUID, TYPE A	2	MISCELLANEOUS	
BRAKE FLUID, (H.D.)	3-4	CLOROX, 5%	4
		CALCIUM SOLUTION SATURATED SOLUTION	4
BUTANE	4	HYDROGEN DISULFIDE, 5%	5
CARBON TETRACHLORIDE	2	SODIUM CHLORIDE SATURATED SOLUTION	4
		SYNTHETIC PERSPIRATION	4
CYCLOHEXANONE	1	TIDE DETERGENT, 1%	4
DIMETHYL FORMAMID	1	WATER	4
DIMETHYL SULFOXIDE	1		
1,4-DIOXANE	1		

IMPORTANT: These ratings are based on testing but should be considered a general guide for contact with these chemicals. Due to variances in jobsite conditions, methods and equipment used with these materials, Safewaze makes no guarantees or warranties on the suitability of this product for the user specific applications. Please follow proper product inspection guidelines and competent person judgement to ensure the safety of the user.