



024-4114

D-Plate Anchor

FEATURES:

- Suited for temporary or permanent installation.
- For installation and use on steel surfaces or I-Beams, or in fully cured concrete 3000 PSI or higher.
- Suitable for horizontal lifelines (HLL) or material hauling use.
- (4) 3-3/4" x 1/2" concrete wedge bolt fasteners included.
- For steel installation, use (4) 1/2" diameter grade 8 steel bolts, length dependent on installation location (not included).
- Dimensions: 6" x 6" x 1/4"
- Working Load Limit (WLL):
 - 2000 lbs. (907 kg) in concrete
 - 2500 lbs. (1134 kg) in steel

ATTACHMENT POINT(S):

- 1 D-ring

MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

ITEM WEIGHT:

- 2.6 lbs. (1.2 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)

N/A	

COMPONENT

MATERIAL SPECIFICATION

Base plate with weld	Powder-coated steel
D-ring	Powder-coated steel
Wedge bolt anchor	Grade 2 Steel