



## 025-1756 through 025-1763

### PRO+ Slate Construction Harness: Alu 3D, Alu QC Chest/Legs, Trauma Relief

#### FEATURES :

- Fixed dorsal D-ring
- Integrated SRL channel
- Side positioning D-rings
- Quick-connect chest
- Quick torso adjusters
- Quick-connect legs
- Shoulder pad
- Fixed comfort waist pad
- Removable leg pads
- Integrated Quick-Adjust Trauma Relief packs

#### FALL ARREST POINT(S) :

- 1 Dorsal D-ring
- 1 Integrated SRL channel

#### ITEM WEIGHT :

- 5.7 lbs. (2.6 kg)



**BUILT-IN TRAUMA RELIEF PACKS**

| USER WEIGHT CAPACITY |                          |
|----------------------|--------------------------|
| ANSI                 | 130-310 lbs. (59-141 kg) |
| OSHA                 | Up to 420 lbs. (191 kg)  |

| STANDARD COMPLIANT WITH |                    |
|-------------------------|--------------------|
| ANSI                    | Z359.11-2021       |
| OSHA                    | 1926.502, 1910.140 |

| SIZE(S)  |         |
|----------|---------|
| 025-1756 | X-Small |
| 025-1757 | Small   |
| 025-1758 | Medium  |
| 025-1759 | Large   |
| 025-1760 | X-Large |
| 025-1761 | 2X      |
| 025-1762 | 3X      |
| 025-1763 | 4X      |

| COMPONENT        | MATERIAL SPECIFICATION                    |
|------------------|---|
| Webbing          | Polyester                                 |
| D-ring(s)        | Anodized aluminum                         |
| Adjuster buckles | Anodized aluminum                         |
| Chest connection | Anodized aluminum                         |
| Leg connection   | Anodized aluminum                         |
| SRL channel      | HDPE                                      |
| Pads             | Nubuck synthetic; Spandex; Poly mesh; EVA |
| Belt             | Polyester; Steel; Stainless steel         |